

Model No.	Shearing Capacity (Thickness in mm)		Shearing length (mm)	Rake Angle Fixed (in deg.)	Stroke (per minute)	Back guage range (mm)	Nos. of Hold down	Motor (H.P.)	Overall Dimension			
	Mild Steel 45 g/cm <sup>2</sup>	Stainless steel 72Kg/cm <sup>2</sup>							Length	Width	Height	Weight
12-20G	1	0.5	1250	0.5	45	600	Spring Type	2	1800	850	1000	1000
25-20G	1	0.5	2500	0.5	40	600	Spring Type	2	3250	850	1000	1500
12-14G	2	1	1250	1	45	600	Spring Type	2	1800	850	1000	1200
15-14G	2	1	1500	1	40	600	Spring Type	2	2150	850	1000	1500
20-14G	2	1	2000	1	35	600	Hydro Pneumatic	3	2600	850	1000	1800
25-14G	2	1	2500	1	30	600	Hydro Pneumatic	3	3250	850	1000	2200
15-10G	3.15	2	1500	1,15'	35	600	Hydro Pneumatic	3	2150	950	1000	1500
20-10G	3.15	2	2000	1,15'	30	600	8	5	2600	950	1200	1800
25-10G	3.15	2	2500	1,15'	28	600	11	5	3250	950	1200	2500
30-10G	3.15	2	3000	1,15'	25	600	13	5	3800	950	1200	2800



**MISHRA HYDRAULICS**